



2152 Copper | 20 W max (halogen) | T3 Lamp or LED | LN-10 T3 Hal. Std




2153 Copper | 20 W max (halogen) | T3 Lamp or LED | LN-10 T3 Hal. Std




2152 / 2153	
HOUSING	
» Stamped solid copper	
FINISH	
» Brushed natural copper	
» Will rapidly age to an elegant bronzelike color and may develop areas of patina over time	
SOCKET/LAMP HOLDER	
» Proprietary ceramic socket	» Stainless steel springs
» Nickel contacts	» Teflon-jacketed wire leads
LENS	
» Clear	
» High impact polycarbonate	
LAMP TYPE	
» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.	
PHOTOMETRICS	
» For photometric data, see pages 131-149.	
MOUNTING	
» Solid brass loop	
» 6' Stainless steel cable hanger	
FASTENERS	
» Stainless steel fasteners	
WIRING	
» Prewired with a three-foot pigtail of 18-2 SPT 1 UV resistant cable and underground connectors for a secure connection to the supply cable.	

2150 / 2151	
HOUSING	
» Extruded solid copper	» Brass base
» Heavy gauge	
FINISH	
» Brushed natural copper	
» Will rapidly age to an elegant bronzelike color and may develop areas of patina over time	
SOCKET/LAMP HOLDER	
» Top grade ceramic socket	» Stainless steel springs
» Nickel contacts	» Teflon-jacketed wire leads
LENS	
» Soda-lime glass	» Shock- and heat-resistant
» Clear	» For optical effect lenses, see ordering information.
» Tempered	
LAMP TYPE	
» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.	
PHOTOMETRICS	
» For photometric data, see pages 131-149.	
MOUNTING	
2150	2151
» Solid brass loop	» Adjustable bracket
» 6' Stainless steel cable hanger	» Junction box
FASTENERS	
» Stainless steel and brass fasteners	
WIRING	
» Prewired with a three-foot pigtail of 18-2 SPT 1 UV resistant cable and underground connectors for a secure connection to the supply cable.	

2150 Copper | 35 W max (hal.) | MR-16 Lamp or LED | LN-20 BAB Hal. Std



2151 Copper | 35 W max (hal.) | MR-16 Lamp or LED | LN-20 BAB Hal. Std



LED SPECIFICATIONS Look for this mark on products where LED options are available.

LED Lamp	Integrated LED
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.	High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column **example: HT-2152-CSN-10 T3**

Mounting	No.	Finish	Lamp	Lenses/Accessories
HT Brass loop with stainless steel cable hanger	2150 2152 * 2153 *	CSN Natural copper	LAMP See reference codes, pages 128-130	BL Flat Cool Blue Lens SL Flat Spread Lens FR Flat Frosted Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb Louver
DL Adjustable bracket and J-box	2151		INTEGRATED LED See reference codes, page 130, group B	

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.
 * The only optional lens available for 2152 and 2153 is Flat Frosted lens.
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.