



MODEL 7218 | Specification Sheet
Residential Series • Path & Area

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



| | |
|------------|-------------------|
| Wattage | 1 – 5 W |
| Voltage | 9 – 15 VAC |
| Housing | Aluminum |
| Dimensions | 6 ¼" DIA x 8 ½" H |



ORDERING INFORMATION

EXAMPLE: PR-7218-B-W-LB5ND

| MOUNTING | MODEL | FINISH | LED |
|----------|-------|--------|-----|
| PR | 7218 | | |

| MOUNTING | MODEL | FINISH | LED | ORDERING NOTES |
|-----------------------|-------|-------------------------------|---|--|
| PR ABS Ground Stake | 7218 | B Black | W-LB2ND 2.5 Watts Warm Integrated LED | Fixtures shipped with specified mounting hardware. Custom length stems available - Consult local distributor. |
| | | Z Architectural Bronze | N-LB2ND 2.5 Watts Neutral Integrated LED | |
| | | DZ Dark Bronze | C-LB2ND 2.5 Watts Cool Integrated LED | |
| | | GT Granite | W-LB5ND 5 Watts Warm Integrated LED | |
| | | W White | N-LB5ND 5 Watts Neutral Integrated LED | |
| | | BR Architectural Brick | C-LB5ND 5 Watts Cool Integrated LED | |
| | | LZ Light Bronze | 150-W-G4 1.5 Watts Warm G4 LED Lamp | |
| | | SB Special Bronze | NL No Lamp | |
| | | GG Glossy Gray | | |
| | | R Rust | | |
| | | HG Hunter Green | | |
| | | WB Weathered Bronze | | |
| | | WI Weathered Iron | | |
| | | GM Graphite Metallic | | |
| | | G Verde | | |
| P Pewter | | | | |
| M Mocha | | | | |
| OF Olde Finish | | | | |



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

