



MODEL 5014i-BSO | Specification Sheet
Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1.5 – 3.5 W
Voltage	9 – 15 VAC
Lumens	180 – 400 Delivered Lumens
Distribution	25° (SP), 36° (MF), 60° (WF)
CCT	3000K, 4000K, 5000K
CRI	80 CRI min.
Housing	Die-cast Brass
Dimensions	2 1/8" DIA x 5 1/4" D



ORDERING INFORMATION

EXAMPLE: GR-5014i-BSO-2.5-W-SP-HL

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	DISTRIBUTION	ACCESSORIES
	5014i	BSO		W		

MOUNTING	MODEL	FINISH	WATTAGE
GR ABS Ground Stake WR Wall-Mount Canopy TR Tree-Mount Junction Box	5014i	BSO Olde Brass	1.5 1.5 Watts 2.5 2.5 Watts 3.5 3.5 Watts
COLOR TEMPERATURE	DISTRIBUTION	ACCESSORIES	ORDERING NOTES
W 3000K N 4000K C 5000K	SP 25° Spot MF 36° Flood WF 60° Wide Flood	FR Frosted Lens LSF Linear Spread Lens 5 5' Wire Lead	Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast Brass.

FINISH:

Olde Brass.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Die-cast Brass knuckle with 1/2" NPS thread.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Performance LED.
180 – 400 Lumens delivered.
1.5 – 3.5 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

COLOR RENDERING:

80 CRI minimum

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Spot **SP** (25°)
Medium Flood **MF** (36°)
Wide Flood **WF** (60°)

DIMENSIONS

