

PRODU	JCT FE	ATURES
-------	--------	---------------



Voltage 9 – 15 VAC

Lamp Type PAR36 LED Lamp Compatible

Housing Die-cast Aluminum

Dimensions 5" DIA x 8" D



ORDERING INFORMATION

EXAMPLE: GR-5237-B-NL

MOUNTING	MODEL	FINISH	LED
	5237		NL

MOL	INTING	MODEL	FINIS	SH	LED	ORDERING NOTES
GR	ABS ground stake	5237	В	Black	NL No Lamp	Fixtures shipped with specified
WR	Wall-mount canopy		z	Architectural Bronze		mounting hardware.
TR	Tree-mount junction box		DZ	Dark Bronze		
			GT	Granite		
			w	White		
			BR	Architectural Brick		
			LZ	Light Bronze		
			SB	Special Bronze		
			GG	Glossy Gray		
			R	Rust		
			HG	Hunter Green		
			WВ	Weathered Bronze		
			wı	Weathered Iron		
			GМ	Graphite Metallic		
			G	Verde		
			P	Pewter		
			м	Mocha		
			OF	Olde Finish		



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

FASTENERS/INSERTS:

All fasteners are stainless steel.

WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

PAR36 LED Lamp Compatible

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

DIMENSIONS





