



MODEL 4260 | Specification Sheet

Residential Series • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 W
Voltage	9 – 15 VAC
CCT	3000K (WARM) 5000K (COOL)
Faceplate	Aluminum, Brass, Copper or Stainless Steel
Dimensions	5 3/4" L x 1" H x 3 1/4" D

ORDERING INFORMATION

EXAMPLE: **SL-4260-BSN-W-LB2ND**

CATEGORY	MODEL	FINISH	LED
SL	4260		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4260	B Black	W-LB2ND 1 Watt Warm Integrated LED C-LB2ND 1 Watt Cool Integrated LED
		R Rust	
		Z Architectural Bronze	
		HG Hunter Green	
		DZ Dark Bronze	
		WB Weathered Bronze	
		GT Granite	
		WI Weathered Iron	
		W White	
		GM Graphite Metallic	
		BR Architectural Brick	
		G Verde	
		LZ Light Bronze	
		P Pewter	
		SB Special Bronze	
		M Mocha	
		GG Glossy Gray	
		OF Olde Finish	
		BSN Natural Brass	
		CSN Natural Copper	
		BSO Olde Brass	
		SS Stainless Steel	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction
of the fixture shown without further notification.



SPECIFICATIONS

FACEPLATE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FLANGE CONSTRUCTION:

Aluminum, Brass, Copper or Stainless Steel.

FINISH:

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Integrated LED Module.
1 Watt.

COLOR TEMPERATURE:

3000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

