



MODEL SM-4246 | Specification Sheet
Residential Series • Brass & Copper • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	5 W
Voltage	9 – 15 VAC
Housing	Brass
Dimensions	9 1/8" L x 2 7/8" H x 7/8" D

ORDERING INFORMATION

EXAMPLE: **SM-4246-BSO-5-W**

CATEGORY	MODEL	FINISH	LED
SM	4246		

CATEGORY	MODEL	FINISH	LED
SM Surface Mount Step Light	4246	BSO Olde Brass	5-W 5 Watts Warm Integrated LED
		B Black	
		DZ Dark Bronze	
		GT Granite	
		W White	
		BR Architectural Brick	
		LZ Light Bronze	
		SB Special Bronze	
		GG Glossy Gray	
		R Rust	
		HG Hunter Green	
		WB Weathered Bronze	
		WI Weathered Iron	
		GM Graphite Metallic	
		G Verde	
P Pewter			
M Mocha			
OF Olde Finish			



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast solid brass.

FINISH:

Olde Brass.
Optional powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Integrated LED Module. 5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

