

TYPE:	MODEL:

I KODOCI I EAIOKE	Ρ	RO	DU	CT	FEAT	URES
-------------------	---	----	----	----	------	------



Wattage	5 W
Voltage	9 – 15 VAC
ССТ	3000K (WARM) 4000K (NEUTRAL) 5000K (COOL)
Housing	Brass or Stainless Steel
Dimensions	21/2" DIA x 21/2" D

ORDERING INFORMATION

EXAMPLE: UW-2118-BSN-W-LC5ND

CATEGORY MODEL FINISH LED

UW 2118

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2118	BSN Natural Brass	W-LC5ND 5 Watts Warm Integrated LED	2118 NOT for use in swimming
		SS Stainless Steel	N-LC5ND 5 Watts Neutral Integrated LED	pools or spas.
			C-LC5ND 5 Watts Cool Integrated LED	

SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

LENS:

Clear, tempered soda-lime glass lens.

FASTENERS:

All fasteners are stainless steel.

WIRING

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable. Connectors for a required above-water connection are also included.

LED

Integrated LED Module. 5 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing. **NOT** for use in swimming pools or spas.

DIMENSIONS



