



MODEL 6570 | Specification Sheet

Residential Series • Path & Area

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

| | |
|------------|-----------------------------|
| Wattage | 1 W |
| Voltage | 9 – 15 VAC |
| CCT | 3000K (WARM) 5000K (COOL) |
| Housing | Aluminum |
| Dimensions | 1½" W x 7" D x 20" H |



ORDERING INFORMATION

EXAMPLE: **PR-6570-B-W-LB2ND**

| MOUNTING | MODEL | FINISH | LED |
|----------|-------|--------|-----|
| PR | 6570 | | |

| MOUNTING | MODEL | FINISH | LED | ORDERING NOTES |
|---------------------|-------|-------------------------------|-----------------------------------------------|------------------------------------------------------------|
| PR ABS Ground Stake | 6570 | B Black | W-LB2ND 1 Watt Warm Integrated LED | Fixtures shipped with specified mounting hardware. |
| | | Z Architectural Bronze | C-LB2ND 1 Watt Cool Integrated LED | |
| | | DZ Dark Bronze | | Custom length stems available - Consult local distributor. |
| | | GT Granite | | |
| | | W White | | |
| | | BR Architectural Brick | | |
| | | LZ Light Bronze | | |
| | | SB Special Bronze | | |
| | | GG Glossy Gray | | |
| | | R Rust | | |
| | | HG Hunter Green | | |
| | | WB Weathered Bronze | | |
| | | WI Weathered Iron | | |
| | | GM Graphite Metallic | | |
| | | G Verde | | |
| | | P Pewter | | |
| | | M Mocha | | |
| | | OF Olde Finish | | |



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

STEM CONSTRUCTION:

1" x 1.5" aluminum tube.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Textured, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem fitted with 1/2" NPT Brass Connection.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Integrated LED Module.
1 Watt.

COLOR TEMPERATURE:

3000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

