



MODEL 4217 | Specification Sheet

Residential Series • Specialty / Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Injection-Molded Polymer
Dimensions	4 ¾" DIA x 3" H



ORDERING INFORMATION

EXAMPLE: UW-4217-B-W-LB5ND-DBL

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	4217	B		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater	4217	B Black	W-LB2ND 2.5 Watts Warm Integrated LED	DBL Dark Blue Lens GL Dark Green Lens RL Red Lens YL Amber Lens
			N-LB2ND 2.5 Watts Neutral Integrated LED	
			C-LB2ND 2.5 Watts Cool Integrated LED	
			W-LB5ND 5 Watts Warm Integrated LED	
			N-LB5ND 5 Watts Neutral Integrated LED	
			C-LB5ND 5 Watts Cool Integrated LED	
			150-W-G4 1.5 Watts Warm G4 LED Lamp	ORDERING NOTES 4217 NOT for use in swimming pools or spas.
			NL No Lamp	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded polymer.

LENS CONSTRUCTION:

Injection-molded polycarbonate.

FINISH APPEARANCE:

Water chemistry (including dissolved chemicals, soluble salts, or tannins) may cause cosmetic changes to the fixture over time. These changes do not affect light output or performance. This fixture is not intended for use in swimming pools or spas.

LENS:

Clear prismatic spread lens.
Optical effect lenses are available.

REFLECTOR:

Removable mirror-finish reflector to block up light and provide wider horizontal spread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.
Connectors for a required above-water connection are also included.

CAUTION:

Follow installation instructions as well as local electrical codes when installing.
NOT for use in swimming pools or spas.

CERTIFICATIONS | STANDARDS | COMPLIANCE:

- Buy American Act (BAA)
- Build America, Buy America Act (BABA)

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing.
NOT for use in swimming pools or spas.

DIMENSIONS

