



**MODEL 5212** | Specification Sheet  
Residential Series • Up / Accent / Downlight

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Voltage	9 – 15 VAC
Lamp Type	T4 LED Lamp Compatible
Housing	Die-cast Aluminum
Dimensions	8" W x 4" H x 4 7/8" D



**ORDERING INFORMATION**

EXAMPLE: GR-5212-B-NL-FR

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
	5212		NL	

MOUNTING	MODEL	FINISH	LED	ACCESSORIES	ORDERING NOTES
<b>GR</b> ABS ground stake <b>WR</b> Wall-mount canopy <b>TR</b> Tree-mount junction box	5212	<b>B</b> Black <b>Z</b> Architectural Bronze <b>DZ</b> Dark Bronze <b>GT</b> Granite <b>W</b> White	<b>BR</b> Architectural Brick <b>LZ</b> Light Bronze <b>SB</b> Special Bronze <b>GG</b> Glossy Gray <b>R</b> Rust <b>HG</b> Hunter Green <b>WB</b> Weathered Bronze <b>WI</b> Weathered Iron <b>GM</b> Graphite Metallic	<b>G</b> Verde <b>P</b> Pewter <b>M</b> Mocha <b>OF</b> Olde Finish	
<b>LED</b>		<b>ACCESSORIES</b>		<b>ORDERING NOTES</b>	
<b>NL</b> No Lamp		<b>FR</b> Frosted Lens <b>HL</b> Honeycomb louver <b>5</b> 5' Wire Lead		Fixtures shipped with specified mounting hardware.  If fixture is to be used in conjunction with Extended Arm Mount ( <b>EAM</b> ): Must specify with extended wire length	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

### FASTENERS/INSERTS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

T4 LED Lamp Compatible

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

