



ITT Series | Specification Sheet
Residential Series • Transformer

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	300 – 600 W
Secondary Voltage	12 VAC
Housing	Injection-Molded Polymer
Dimensions	11" L x 7" W x 7 1/2" D



ORDERING INFORMATION

SERIES **MODEL** **COVER FINISH** *EXAMPLE: ITT-600-B*

ITT

SERIES	MODEL	COVER FINISH
ITT 12 Volt Tri-Tap Transformer	300 300 Watts	B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White
	600 600 Watts (300 W x 2)	
		BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic
		G Verde P Pewter M Mocha OF Olde Finish



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.
Integrally molded waterproof compartments separate transformer chamber from splice compartment.

COVER CONSTRUCTION:

Injection-molded glass-reinforced polymer.
Cover is equipped with glass viewfinder inspection window, which allows for circuit breaker "on / off" inspections without removing cover.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

PRIMARY PROTECTION:

Auto thermal shut-off

SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker.
Fully grounded and isolated with encapsulated core and coil.

WIRING:

Splice compartment has two 3/4" NPT conduit entries for through wiring and one 1/2" NPT entry. Potting compound for wiring compartment supplied with unit.

FASTENERS/INSERTS:

All fasteners are stainless steel with brass inserts.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for landscape lighting transformers (UL 1838).

Pool & Spa Ready - Suitable for Use with Submersible Luminaires (power cord must be shortened to a 3-foot maximum length - see Installation Instructions).

AVAILABLE POWER RATING:

300 or 600 Watts

PRIMARY VOLTAGE:

120 Volts
(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

SECONDARY VOLTAGE:

11, 12 and 13 Volts

DIMENSIONS

