



MODEL 8205 | Specification Sheet
Residential Series • Bollard

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	1.5 W
Voltage	9 – 15 VAC
Lamp Type	G4 LED
Housing	Aluminum
Dimensions	9" DIA x 26 1/2" H



ORDERING INFORMATION

EXAMPLE: PR-8205-B-150-W-G4-RS

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
BR	8205			

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
BR Mounting Base with ABS ground stake	8205	B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic G Verde P Pewter M Mocha OF Olde Finish	150-W-G4 1.5 Watts Warm G4 LED Lamp NL No Lamp	RS 180° Reflector Shield



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

POST CONSTRUCTION:

Extruded Aluminum (1/8" wall thickness).

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Frosted, high-impact polycarbonate lens.

MOUNTING:

Aluminum mounting base with ABS ground stake included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

G4 LED Lamp.
1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

