

| TYPE:    | MODEL: |
|----------|--------|
|          |        |
| PROJECT: |        |
|          |        |

# **PRODUCT FEATURES**





| Wattage    | 4.5 W or 5.5 W (x2)       |
|------------|---------------------------|
| Voltage    | 9 – 15 VAC                |
| Lumens     | 295 or 389 Lumens         |
| Lamp Туре  | MR-16 LED (x2)            |
| Housing    | Aluminum, Brass or Copper |
| Dimensions | 2½" DIA x 6¼" H x 4½" D   |

# **ORDERING INFORMATION**

EXAMPLE: **WR-2522-B-4.5-W-36-FR** 

CATEGORY MODEL FINISH LED ACCESSORIES
WR 2522

| CATEGORY N       | MODEL F | FINISH |                      |     | LED               |          | ACCESSORIES                        |     |                      |
|------------------|---------|--------|----------------------|-----|-------------------|----------|------------------------------------|-----|----------------------|
| WR Wall-Mount 25 | 522     | В      | Black                | R   | Rust              | 4.5-W-15 | 4.5 Watts   Warm   15° Narrow Spot | FR  | Frosted Lens         |
|                  |         | z      | Architectural Bronze | HG  | Hunter Green      | 4.5-W-25 | 4.5 Watts   Warm   25° Spot        | BL  | Flat Cool Blue Lens  |
|                  |         | DZ     | Dark Bronze          | WB  | Weathered Bronze  | 4.5-W-36 | 4.5 Watts   Warm   36° Flood       | SL  | Flat Spread Lens     |
|                  |         | GT     | Granite              | WI  | Weathered Iron    | 4.5-W-60 | 4.5 Watts   Warm   60° Wide Flood  | DBL | Flat Dark Blue Lens  |
|                  |         | w      | White                | GM  | Graphite Metallic | 5.5-W-15 | 5.5 Watts   Warm   15° Narrow Spot | GL  | Flat Dark Green Lens |
|                  |         | BR     | Architectural Brick  | G   | Verde             | 5.5-W-25 | 5.5 Watts   Warm   25° Spot        | RL  | Flat Red Lens        |
|                  |         | LZ     | Light Bronze         | P   | Pewter            | 5.5-W-36 | 5.5 Watts   Warm   36° Flood       | YL  | Flat Amber Lens      |
|                  |         | SB     | Special Bronze       | М   | Mocha             | 5.5-W-60 | 5.5 Watts   Warm   60° Wide Flood  | HL  | Honeycomb louver     |
|                  |         | GG     | Glossy Gray          | OF  | Olde Finish       | NL       | No Lamp                            |     |                      |
|                  |         |        |                      |     |                   |          |                                    |     |                      |
|                  | E       | BSN    | Natural Brass        | CSN | Natural Copper    |          |                                    |     |                      |
|                  | E       | BSO    | Olde Brass           | SS  | Stainless Steel   |          |                                    |     |                      |
|                  |         |        |                      |     |                   |          |                                    |     |                      |



## **SPECIFICATIONS**

## **HOUSING CONSTRUCTION:**

Available in Aluminum, Brass or Stainless Steel.

### FINISH

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LENS

Clear, tempered glass lens. Optical effect lenses are available.

### MOUNTING:

Adjustable bracket included.

### **FASTENERS/INSERTS:**

All fasteners are stainless steel.

## LED:

MR-16 LED Lamp (*x2*). 295 or 389 Lumens (*x2*). 4.5 or 5.5 Watts (*x2*).

## **ELECTRICAL:**

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

### WIRING:

Prewired with a 12" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

## **CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

## LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°) Narrow Spot **25** (25°) Medium Flood **36** (36°) Wide Flood **60** (60°)

## **DIMENSIONS**



