



MODEL 5232 | Specification Sheet
Residential Series • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Die-cast Aluminum
Dimensions	5" DIA x 4 3/8" D



ORDERING INFORMATION

EXAMPLE: *SL-5232-B-4.5-W-36-CFR*

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
	5232			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
SL Step Light	5232	B Black	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	CBL Crowned Cool Blue Lens BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb Louver JBCP-150 Concrete Mounting Kit
		Z Architectural Bronze	4.5-W-25 4.5 Watts Warm 25° Spot	
		DZ Dark Bronze	4.5-W-36 4.5 Watts Warm 36° Flood	
		GT Granite	4.5-W-60 4.5 Watts Warm 60° Wide Flood	
		W White	5.5-W-15 5.5 Watts Warm 15° Narrow Spot	
		BR Architectural Brick	5.5-W-25 5.5 Watts Warm 25° Spot	
		LZ Light Bronze	5.5-W-36 5.5 Watts Warm 36° Flood	
		SB Special Bronze	5.5-W-60 5.5 Watts Warm 60° Wide Flood	
		GG Glossy Gray	NL No Lamp	
		R Rust		
		HG Hunter Green		
		WB Weathered Bronze		
		WI Weathered Iron		
		GM Graphite Metallic		
		G Verde		
		P Pewter		
		M Mocha		
		OF Olde Finish		



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

LENS COVER CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Frosted, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

Recessed mounting box has two 1/2" NPT inlets.
Optional concrete mounting kit available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

DIMENSIONS

