

TYPE:	MODEL:

PRODUCT FEATURES

Wattage	1.5 W
Voltage	9 – 15 VAC
Lamp Туре	G4 LED
Housing	Aluminum
Dimensions	10 ¼" W x 25 %" H (above grade) 37 %" H (over all)

8240



EXAMPLE: **PR-8240-B-150-W-G4-RS**

ORDERING INFORMATION

BR

MOUNTING MODEL FINISH LED

MOUNTING	MODEL	FINISH		LED	
BR Direct-burial Post	8240	В	Black	150-W-G4	1.5 Watts Warm G4 LED Lamp
		z	Architectural Bronze	NL	No Lamp
		DZ	Dark Bronze		
		GT	Granite		
		w	White		
		BR	Architectural Brick		
		LZ	Light Bronze		
		SB	Special Bronze		
		GG	Glossy Gray		
		R	Rust		
		HG	Hunter Green		
		WB	Weathered Bronze		
		wı	Weathered Iron		
		GM	Graphite Metallic		
		G	Verde		
		Р	Pewter		
		м	Mocha		
		OF	Olde Finish		



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

POST CONSTRUCTION:

Extruded Aluminum (1/8" wall thickness).

FINISH

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish

LENS:

Clear, high-impact polycarbonate lens.

MOUNTING:

Direct-burial Post. (Post extended 12" for in-ground or concrete mounting.)

FASTENERS:

All fasteners are stainless steel.

WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

DIMENSIONS



