



**MODEL 2350** | Specification Sheet  
Residential Series • Up / Accent / Downlight

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Solid Brass
Dimensions	2 1/2" DIA x 6 3/4" D

**ORDERING INFORMATION**

EXAMPLE: *GR-2350-BSN-4.5-W-36-FR*

CATEGORY	MODEL	FINISH	LED
	2350		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
<b>GR</b> ABS Ground Stake	<b>2350</b>	<b>BSN</b> Natural Brass	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	<b>BL</b> Flat Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver
<b>WB</b> Brass Wall-Mount Canopy			<b>BSO</b> Olde Brass	
			<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	
			<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	
			<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	
			<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	
			<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	
			<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	
			<b>NL</b> No Lamp	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

**HOUSING CONSTRUCTION:**

Solid Brass.

**FINISH:**

Natural Brass or Olde Brass.

**LENS:**

Clear, tempered glass lens.  
Optical effect lenses are available.

**MOUNTING:**

Solid Brass knuckle with 1/2" NPS thread.

**FASTENERS/INSERTS:**

Fasteners are stainless steel and brass.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

