

TYPE:	MODEL:
PROJECT:	

<b>PRO</b>	DU	ICT	FE	AΤ	URES
------------	----	-----	----	----	------

Wattage	1 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	1½" W x 7" D x 20" H



EXAMPLE: PR-6570-B-W-LB2ND

# **ORDERING INFORMATION**

\_\_\_

MOUNTINGMODELFINISHLEDPR6570

MOUNTING	MODEL	FINISH		LED		ORDERING NOTES
PR ABS Ground Stake 6570	6570	В	Black	W-LB2ND	1 Watt   Warm   Integrated LED	Fixtures shipped with specified mounting hardware.
		z	Architectural Bronze	C-LB2ND	1 Watt   Cool   Integrated LED	
		DZ	Dark Bronze			Custom length stems available - Consult local distributor.
		GT	Granite			
		w	White			
		BR	Architectural Brick			
		LZ	Light Bronze			
		SB	Special Bronze			
		GG	Glossy Gray			
		R	Rust			
	HG	Hunter Green				
		WB	Weathered Bronze			
		wı	Weathered Iron			
		GM	Graphite Metallic			
		G	Verde			
		P	Pewter			
		м	Mocha			
		OF	Olde Finish			



### **SPECIFICATIONS**

### **HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

### STEM CONSTRUCTION:

1" x 1.5" aluminum tube.

#### **FINISH**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LENS:

Textured, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem fitted with 1/2" NPT Brass Connection.

## LED:

Integrated LED Module.

1 Watt.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

## **FASTENERS:**

All fasteners are stainless steel.

#### WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

#### CERTIFICATION

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**



