



# MODEL 2114 | Specification Sheet

Residential Series • Brass & Copper • Underwater

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
CCT	3000K (WARM)   4000K (NEUTRAL)   5000K (COOL)
Housing	Brass or Stainless Steel
Dimensions	2 7/8" DIA x 2 1/2" D

## ORDERING INFORMATION

EXAMPLE: UW-2114-BSN-W-LB5ND

CATEGORY	MODEL	FINISH	LED
UW	2114		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2114	BSN Natural Brass SS Stainless Steel	W-LB2ND 2.5 Watts   Warm   Integrated LED	2114 <b>NOT</b> for use in swimming pools or spas.
			N-LB2ND 2.5 Watts   Neutral   Integrated LED	
			C-LB2ND 2.5 Watts   Cool   Integrated LED	
			W-LB5ND 5 Watts   Warm   Integrated LED	
			N-LB5ND 5 Watts   Neutral   Integrated LED	
			C-LB5ND 5 Watts   Cool   Integrated LED	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Machined brass or stainless steel.

### LENS:

Clear, tempered soda-lime glass lens.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.

Connectors for a required above-water connection are also included.

### LED:

Integrated LED Module.

2.5 – 5 Watts.

### COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

### CAUTION:

Follow installation instructions as well as local electrical codes when installing.

**NOT** for use in swimming pools or spas.

## DIMENSIONS

