



CTS Series | Specification Sheet
Residential Series • Transformer

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

| | |
|-------------------|-------------------------|
| Wattage | 300 – 1200 W |
| Secondary Voltage | 12 VAC |
| Housing | Stainless Steel |
| Dimensions | 17" H x 9" W x 5 1/2" D |



ORDERING INFORMATION

EXAMPLE: CTS-600DT

SERIES **MODEL** **OPTIONAL FINISH**

CTS

| SERIES | MODEL | OPTIONAL FINISH | ORDERING NOTES |
|--|--|-----------------------------------|---|
| CTS 12 Volt Transformer | 300 300 Watts | Clear powder coat finish standard | <p>* See the following for accessory descriptions:</p> <p>T Removable multi-setting mechanical 24-hour timer</p> <p>DT Removable multi-setting digital 7-day timer</p> <p>DA Removable multi-setting digital astronomical timer</p> <p>RP Remote wired photocell with electronic timer</p> <p>Accessories not required for operation of transformer</p> |
| | 300T 300 Watts T timer * | B Black | |
| | 300DT 300 Watts DT timer * | Z Architectural Bronze | |
| | 300DA 300 Watts DA timer * | DZ Dark Bronze | |
| | 300RP 300 Watts RP photocell * | GT Granite | |
| | 600 600 Watts (300 W x 2) | W White | |
| | 600T 600 Watts (300 W x 2) T timer * | BR Architectural Brick | |
| | 600DT 600 Watts (300 W x 2) DT timer * | LZ Light Bronze | |
| | 600DA 600 Watts (300 W x 2) DA timer * | SB Special Bronze | |
| | 600RP 600 Watts (300 W x 2) RP photocell * | GG Glossy Gray | |
| | 900 900 Watts (300 W x 3) | R Rust | |
| | 900T 900 Watts (300 W x 3) T timer * | HG Hunter Green | |
| | 900DT 900 Watts (300 W x 3) DT timer * | WB Weathered Bronze | |
| | 900RP 900 Watts (300 W x 3) RP photocell * | WI Weathered Iron | |
| | 1200 1200 Watts (300 W x 4) | GM Graphite Metallic | |
| | 1200T 1200 Watts (300 W x 4) T timer * | G Verde | |
| 1200DT 1200 Watts (300 W x 4) DT timer * | P Pewter | | |
| 1200RP 1200 Watts (300 W x 4) RP photocell * | M Mocha | | |
| | OF Olde Finish | | |



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

20-gauge 304 stainless steel.
1/2"- 3/4" knockouts on each side of enclosure for conduit and accessory mounting as well as a removable, swing-down enclosure bottom with Adjustable Cable Raceway Feeder and multiple 1/2"- 3/4" and 2" knockouts.

NEMA ENCLOSURE RATING:

3R

FINISH:

Clear powder coat finish standard. Also available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

TERMINALS:

- Low voltage terminal strip for multiple cable connections
- 120-volt terminal strip for easy hard-wiring and an accessory terminal strip.

PRIMARY PROTECTION:

Auto thermal shut-off

SECONDARY PROTECTION:

Resettable high performance magnetic circuit breaker.
Fully grounded and isolated with encapsulated core and coil.

WIRING:

6-foot, heavy-gauge, grounded, water-resistant power cord with integrally molded plug.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

Pool & Spa Ready - Suitable for Use with Submersible Luminaires (power cord must be shortened to a 3-foot maximum length - see Installation Instructions).

AVAILABLE POWER RATING:

300, 600, 900 or 1200 Watts

PRIMARY VOLTAGE:

120 Volts
(Also available in 208V, 230V or 277V, 50 or 60 cycle - Special order only.)

SECONDARY VOLTAGE:

12 Volts (with High/Low setting)

DIMENSIONS

