



MODEL 5106 | Specification Sheet
Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	2 – 4 W
Voltage	9 – 15 VAC
CCT	3000K, 4000K, 5000K
Housing	Die-cast Aluminum
Dimensions	5" W x 3 7/8" H x 2" D



ORDERING INFORMATION

EXAMPLE: GR-5105-B-2-W-FR

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	ACCESSORIES
	5105				

MOUNTING	MODEL	FINISH		
GR ABS ground stake WR Wall-mount canopy TR Tree-mount junction box	5106	B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White	BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic	G Verde P Pewter M Mocha OF Olde Finish

WATTAGE	COLOR TEMPERATURE	ACCESSORIES	ORDERING NOTES
2 2 Watts 3 3 Watts 4 4 Watts	W 3000K N 4000K C 5000K	FR Frosted Lens 5 5' Wire Lead	Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length Wireless Control RGBW Smart LED available. Consult Vista Customer Service for details.



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum. Optic and driver compartment environmentally sealed.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Performance LED. 2 – 4 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

