

TYPE:	MODEL:

PRODU	JCT FE <i>F</i>	ATURES
-------	-----------------	--------

Wattage	5 W
Voltage	9 – 15 VAC
ССТ	3000K (WARM) 4000K (NEUTRAL) 5000K (COOL)
Housing	Brass or Stainless Steel
Dimensions	2%" DIA x 3½" D

ORDERING INFORMATION

EXAMPLE: UW-2119-BSN-W-LC5ND

CATEGORY MODEL FINISH LED

UW 2119

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2119	BSN Natural Brass	W-LC5ND 5 Watts Warm Integrated LED	2119 NOT for use in swimming
		SS Stainless Steel	N-LC5ND 5 Watts Neutral Integrated LED	pools or spas.
			C-LC5ND 5 Watts Cool Integrated LED	





SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

LENS:

Clear, tempered soda-lime glass lens.

MOUNTING:

Solid brass or stainless steel mounting bracket allows ±20° of adjustment.

FASTENERS:

All fasteners are stainless steel.

WIRING

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.

Connectors for a required above-water connection are also included.

LED:

Integrated LED Module.

5 Watts.

COLOR TEMPERATURE:

 $3000\mbox{K},\,4000\mbox{K}$ or $5000\mbox{K}$ CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing.

NOT for use in swimming pools or spas.

DIMENSIONS



