




MODEL 2161 | Specification Sheet
Residential Series • Brass & Copper • Path & Area

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Brass and Stainless Steel
Dimensions	4 ½" DIA x 16 ½" H



ORDERING INFORMATION

EXAMPLE: PR-2161-BSN-W-LB5ND

MOUNTING	MODEL	FINISH	LED
PR	2161	BSN	

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2161	BSN Natural Brass and Stainless Steel	W-LB2ND 2.5 Watts Warm Integrated LED
			N-LB2ND 2.5 Watts Neutral Integrated LED
			C-LB2ND 2.5 Watts Cool Integrated LED
			W-LB5ND 5 Watts Warm Integrated LED
			N-LB5ND 5 Watts Neutral Integrated LED
			C-LB5ND 5 Watts Cool Integrated LED
			150-W-G4 1.5 Watts Warm G4 LED Lamp
NL No Lamp			



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stainless Steel shade.
Twist-To-Lock Solid Brass lamp base.

STEM CONSTRUCTION:

1/2" Brass pipe.

LENS:

Textured, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem threaded with 1/2" NPT.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

