

PRODU	JCT FE <i>P</i>	ATURES
-------	-----------------	--------







# **ORDERING INFORMATION**

EXAMPLE: GR-5238-B-NL-FR

**MOUNTING MODEL FINISH** LED **ACCESSORIES** NL 5238

MOU	INTING	MODEL	FINIS	БН	LED	ACC	ESSORIES	ORDERING NOTES
GR	ABS ground stake	5238	В	Black	<b>NL</b> No Lamp	FR	Frosted Lens	Fixtures shipped with specified mounting hardware.
WR	Wall-mount canopy		z	Architectural Bronze		BL	Flat Cool Blue Lens	
TR	Tree-mount junction box		DZ	Dark Bronze		SL	Flat Spread Lens	
			GT	Granite		DBL	Flat Dark Blue Lens	
			w	White		GL	Flat Dark Green Lens	
			BR	Architectural Brick		RL	Flat Red Lens	
			LZ	Light Bronze		YL	Flat Amber Lens	
			SB	Special Bronze		HL	Honeycomb louver	
			GG	Glossy Gray				
			R	Rust				
			НG	Hunter Green				
			WB	Weathered Bronze				
			wı	Weathered Iron				
			GM	Graphite Metallic				
			G	Verde				
			P	Pewter				
			м	Mocha				
			OF	Olde Finish				



## **SPECIFICATIONS**

## HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

#### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

#### LENS

Clear, tempered glass lens. Optical effect lenses are available.

#### MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

## **FASTENERS/INSERTS:**

All fasteners are stainless steel.

## LED:

PAR36 LED Lamp Compatible

#### ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

## WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

## **CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**





