



**MODEL PACK – 3** | Specification Sheet  
Residential Series • Pro Pack

TYPE:  MODEL:

PROJECT:

**PRODUCT DESCRIPTION**



5006-BSO Uplight	Qty 6
2267-BSO Pathlight	Qty 4
ES-150 Transformer	Qty 1
TC-112 Timer	Qty 1
GS-150 ABS Ground Stake	Qty 10
Gel-Filled Underground Connectors	Qty 20



**5006-BSO FEATURES**



LED Type	4.5W   36° LED MR-16
Voltage	9 – 15 VAC
Lumens	295 Lumens
Housing	Die-cast Brass
Finish	Olde Brass
Lens	Clear Tempered Glass
Mounting	Die-cast Brass knuckle with 1/2" NPS thread
Dimensions	2" DIA x 5 3/4" D



**PROFESSIONAL  
OUTDOOR LIGHTING**

**www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)**  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**2267-BSO FEATURES**



LED Type	1.5W LED G4 Bi-Pin
Voltage	9 – 15 VAC
Housing	Die-cast Brass
Finish	Olde Brass
Lens	Clear Polycarbonate
Mounting	Bottom of stem threaded with 1/2" NPT
Dimensions	5 1/2" DIA x 16" H



**ES-150 FEATURES**



Wattage	150 W
Primary Voltage	120 VAC
Secondary Voltage	12 and 15 VAC
Housing	20-gauge 304 stainless steel
Finish	Clear powder coat finish
Nema Enclosure Rating	3R
Dimensions	11 3/4" H x 6 1/8" W x 5 1/4" D





**TC-112 FEATURES**



Input Voltage	120 VAC
Current Rating	9 A
Wattage	1125 W
Program ON/OFF settings	2
Minimum ON/OFF Times	30 min.
Mechanism Type	Analog/Mechanical
Dimensions	3 1/8" H x 3" W x 2" D



**GS-150 FEATURES**



Type	Ground Stake
Material	ABS
Fixture Mounting	1/2" FPT Base
Dimensions	9" H x 2 3/8" DIA

