



MODEL 5285 | Specification Sheet
Residential Series • In-Grade

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	6¾" DIA x 7¾" H

ORDERING INFORMATION

EXAMPLE: **GW-5285-BSN-4.5-W-36-CFR**

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
GW	5285			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
GW In-Grade	5285	BSN Natural Brass BSO Olde Brass SS Stainless Steel	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	CFR Crowned Frosted Lens CBL Crowned Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver
			4.5-W-25 4.5 Watts Warm 25° Spot	
			4.5-W-36 4.5 Watts Warm 36° Flood	
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	
			5.5-W-25 5.5 Watts Warm 25° Spot	
			5.5-W-36 5.5 Watts Warm 36° Flood	
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	
			NL No Lamp	



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

LENS COVER CONSTRUCTION:

Machined Brass or 304 Stainless Steel.

WELL CONSTRUCTION:

6" Black ABS.

FINISH:

Natural Brass, Olde Brass or Natural Stainless Steel lens cover.
Housing available in black only.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

OPTICS/AIMING:

Housing bracket within ABS well provides up to $\pm 45^\circ$ of tilt.
Additionally, the adjustable lamp bracket provides up to $\pm 25^\circ$ of tilt as well as 360° rotation of housing for precise beam control. Lamp bracket can be locked into place to prevent disrupting lamp position when relamping.

MOUNTING:

In-grade. Mounting accessories not required.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

DIMENSIONS

