



MODEL 4208 | Specification Sheet
Residential Series • Path & Area

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	4 3/8" W x 28 1/2" H



ORDERING INFORMATION

EXAMPLE: PR-4208-B-W-LB5ND

MOUNTING	MODEL	FINISH	LED
PR	4208		

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
PR ABS Ground Stake	4208	B Black	W-LB2ND 2.5 Watts Warm Integrated LED	Fixtures shipped with specified mounting hardware. Custom length stems available - Consult local distributor.
		Z Architectural Bronze	N-LB2ND 2.5 Watts Neutral Integrated LED	
		DZ Dark Bronze	C-LB2ND 2.5 Watts Cool Integrated LED	
		GT Granite	W-LB5ND 5 Watts Warm Integrated LED	
		W White	N-LB5ND 5 Watts Neutral Integrated LED	
		BR Architectural Brick	C-LB5ND 5 Watts Cool Integrated LED	
		LZ Light Bronze	150-W-G4 1.5 Watts Warm G4 LED Lamp	
		SB Special Bronze	NL No Lamp	
		GG Glossy Gray		
		R Rust		
		HG Hunter Green		
		WB Weathered Bronze		
		WI Weathered Iron		
		GM Graphite Metallic		
		G Verde		
P Pewter				
M Mocha				
OF Olde Finish				



PROFESSIONAL OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

STEM CONSTRUCTION:

¼" schedule-40 aluminum pipe.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Clear, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem fitted with ½" NPT Bushing.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

